

# AXPERT-*i-Sine*

## ACTIVE FRONT-END CONVERTER

Active Front-end Converter is an IGBT based AC to DC converter. It keeps supply side power factor to unity and supply current sinusoidal. AFC also regenerates the excessive power from DC link capacitor to grid side and so it is also popularly known as Regenerative Unit. A single unit of high capacity can also be used for multiple VFD (Variable Frequency Drive) of low capacity having common DC bus configuration.

Six pulse diode rectifier bridge is a basic building block of many products such as UPS, battery chargers, VFDs, DC drives etc., known as non-linear loads. They generate about 70...120 % current harmonic distortion at the input.

AFC reduces the current harmonic distortion level to  $< 5\%$ . It is a high quality product and meets the international power quality standards such as IEEE 519-2014.

### AFC Benefits

- Feeds back the excess power to grid from regenerative loads, connected at the VFD output
- Reduces total harmonic distortion to draw sine wave current from the utility
- Stabilizes output DC voltage against mains and load fluctuations
- Improves power factor to unity
- Compatible with any VFD, useful in common DC applications

### Target Applications

- Centrifuges
- Cranes and hoists
- Un-winders
- Paper machines
- Regenerative application
- Roller tables
- Test jigs for dynamometers, gears and motor test benches



**“Feeds back excess power with improved quality”**

# Standard Specifications

<b>Electrical</b>																					
Input voltage/ frequency	440, <b>460</b> , 480 VAC (-10 %, +5 %), 3-Phase, 3-Wire, 60 Hz (±5 %)																				
Output voltage	660, <b>690</b> , 720 VDC (according to input voltage), (+2 %)																				
AMT-AFC-XXX-4	018	022	030	037	045	055	075	090	110	132	160	200	250	315	355	400	450	500 <sup>#</sup>			
Converter capacity (kVA)	22	25	36	43	50	61	83	101	122	144	176	219	273	341	388	438	492	546			
Max. continuous rated current (A)	26	31	42	52	63	77	104	125	152	182	220	274	343	432	486	548	616	685			
AFC current for 60 second (A)	36	42	60	72	84	102	138	168	204	240	294	366	456	570	648	732	822	912			
Applicable VFD capacity (HP)	25	30	40	50	60	75	100	125	150	200	250	300	400	450	500	550	600	700			
Weight (kg/lb)	50/110	52/114	55/121	55/121	60/132	65/143	195/430	210/463	225/496	250/551	300/661	335/738	360/794	410/904	Consult factory						
Frame size	A							B							Consult factory						
<b>Control functions*</b>																					
Control mode & method	Constant Voltage & Hysteresis current control																				
Input current distortion (% THD)	Less than 5 % (at 100 % load)																				
Input power factor	0.99 (at 100 % load & nominal voltage), better than 0.95 (at load of more than 30 %)																				
Regeneration mode	Yes (Automatic)																				
Max. switching frequency	5 kHz																				
Efficiency	Approx. 98 %																				
<b>Operation specifications</b>																					
Digital inputs	5-Programmable sequence inputs, sink / source and Active Close / Active Open selectable																				
Digital outputs	4-Programmable sequence outputs, open collector type																				
Potential free contacts	3-programmable relays:	1-NO, 1-NC for 5 A @ 240 Vac Programmable between 12 different options																			
Programmable analog outputs	2-Programmable analog outputs AO1 & AO2: Voltage (0...10) V / Current (4...20) mA with settable Gain, Bias, Min. and Max. scaling																				
Soft-charge	Through resistor within 5 sec.																				
Auto start	Yes, AFC can start at power ON condition in local and serial mode.																				
Auto restart	Adjustable up to ten times for fault like Over current fault, Timed over current fault, Adjustable over current fault, DC bus over voltage fault, DC bus under voltage fault, Earth fault, Temperature fault, External fault, R-Phase Temp Fault, Y-Phase Temp Fault, B-Phase Temp Fault.																				
<b>Display indications</b>																					
Display and keypad module	Digital Operation Panel 128 x 64 Graphical LCD with white back light LED, 8-Key keypad, 3-Status indicating LED for Run, Stop and Fault; Real Time Clock.  $V_{Lr}$ , THD <sub>r</sub> , THD <sub>s</sub> , Line Frequency, DC bus voltage, PF, DPF, kW, kWh import, kWh export, kWh net, kVA, kVAR, Source side current for each phase																				
<b>Communication</b>																					
Network connectivity	RS-485 for PC interface with Modbus-RTU protocol and Wi-Fi connectivity as standard. (DeviceNet, Profibus DP (Slave), CANopen, Ethernet, ControlNet are optional)																				
<b>Protective specifications</b>																					
Protective function	Over current	Adjustable over current							DC bus under voltage							External fault					
	Timed over current	DC bus over voltage							Over temperature							Charging fault					
	DC bus over voltage	Ground fault							Phase loss							EEPROM fault					
	Fault history	Last 20 faults with status at time fault occurred stored in memory																			
Electronic thermal overload	120 % Overload for 60 Seconds																				
<b>Environment</b>																					
Installation location	Indoor																				
Type of cooling	Forced Air Cooling																				
Ambient temperature	5...113 °F (-15...45 °C)																				
Storage temperature	-4...158 °F (-20...70 °C)																				
Audible noise	≤ 72 db @ 3 ft (1.0 m)																				
Altitude (above sea level)	3300 ft (1000 m) without derating, derate 1 % per 330 ft (100 m) above 3300 ft (1000 m)																				
Model derating with temperature	Above 113 °F (45 °C), derate the output current by 1.8 °F (3 % / 1 °C) Maximum up to 131 °F (55 °C) temperature																				
Relative humidity	0...95 % max non condensing																				
<b>Mechanical specifications</b>																					
Color	Frame A: Aluzinc enclosure with Amtech green front cover Frame B: RAL 7035																				
Dimensions in inch (mm) (W X D X H)	A = 12.2 X 14.2 X 35.4 (310 X 360 X 900), IP 00, Wall mounting B = 23.6 X 23.6 X 78.6 (600 X 600 X 1995), IP 31, Floor mounting																				
<b>Reference standard</b>																					
Harmonic	IEEE 519-2014, G5/4-1, GB/T 14549-93, IEC 61000-3-2, IEC 61000-3-4, IEC 61000-3-12																				
Safety	IEC 50178																				

\* All performance specifications are valid at nominal ratings.

# Consult AMTECH for above 500 kW rating and line supply voltages 575 V or 690 V.

Specifications in this catalog are subject to change without notice.

CAT.NO. : ADI/AFC/01-26



745 Trabert Ave NW  
Atlanta, GA. 30318  
Phone : (770) 8AMTECH  
          : (770) 826-8324  
E-mail : info@amtechdrives.com  
URL : www.amtechdrives.com

